



Swiftpro K60 Single and Double Sided **Retransfer Card Printer**

The Swiftpro K60D retransfer card printer has an outstanding print quality for single and double sided printing. With 600dpi printing density, it is the ideal solution for organisations requiring high-quality identification cards, financial debit and credit cards along with all forms of citizen ID, such as national ID, driving license and military ID.

The Swiftpro K60D retransfer card printer has an outstanding print quality for single and double sided printing. With 600dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalised physical and logical access management.

The ultra-fast, powerful Swiftpro K60D printer is available with contact and contactless smart card encoding technologies and 100 cards input and output hopper with optional 250 hopper upgrade. This reliable and durable printer is the ideal solution for both entry level to advanced secure card programs for a range of vertical markets.

Selecting the right printer is important, more important is ensuring the supply of Genuine Swiftpro Supplies and Retransfer film is also critical in delivering reliability, print quality and vibrant colours for your card programs. Swiftpro supplies deliver consistency and ensure the longevity of your printer and print head and minimise downtime and create efficiencies in your card programs. Always ask for Genuine Swiftpro Supplies from your Authorised Premiere Value Added Distributor, Premiere Enterprise Solution Provider or Premiere Value-Added Reseller.



SECURITY

The ribbon erase function prevents leakage of personal information on the monochrome panel ink ribbon. It scrambles information beyond recognition to protect this data.



VERSATILITY

Swiftpro's modular design permits customers to upgrade as their card programs need changes.



IMAGE QUALITY

High Resolution printing using 600dpi printing provides superior print quality for all your card programs.



RELIABILITY

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.



INNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organisations since 1989.



DURABILITY

Highly durable printers with industry leading warranties on all our products and lifetime on the print head. The K60D comes with an optional single or dual sided laminator providing elevated durability and Security to your card program.

Swiftpro K60 Single and Double Sided Retransfer Card Printer



Optional Laminator



CORPORATE



EDUCATION



FINANCE



HEALTHCARE



RETAIL



TRANSPORT



GOVERNMENT

Printing

Dye Sublimation Retransfer
Full Color Retransfer printing
Single and Double Sided Printing
130 cards per hour/30 seconds per card (YMCK)
180 cards per hour/20 seconds monochrome Black
256 Graduation Printing
Over the Edge Printing on CR80, ID-1 Cards

Standard Features

USB & Ethernet connectivity
100 Input Hopper (30mil)
100 Output Hopper (30mil)
LCD Panel
600 DPI Print Resolution
36 Month Printer Warranty
Lifetime Printhead Warranty
Microsoft Windows Driver
Solenoid Electronic Locks for Input Hopper
Solenoid Electronic Locks for Supplies / Front Door Housing
Controlling Lock/Unlock from Status Monitor
K Ribbon Erase Function
IpSec Security for Secure Data Encryption IPv6 and IPv4
Inline Bend Remedy
MAC Address Forced Printing (UV Panel on Card)
Kensington Locks

Optional Encoding

Magnetic Stripe ISO High/Low Coercivity Encoder
Contactless Encoder (iClass, Mifare and Desfire)
Contact Encoder (CF-7CRW / Control board)
Contact Encoder (CF-7CCS / IC Contact Station)

Software Supported

SwiftCredential

CardPresso

Card Exchange

All Card Personalisations software used through Swiftpro Driver*

*check with Software vendor and some feature may be limited for use on Swiftpro Printers

Microsoft® Windows® 7, 8, 10, 11 32bit / 64bit

Microsoft® Windows® Server 2008 R2 (SPI) 64bit

Microsoft® Windows® XP Server 2012 64bit

Swiftpro Genuine Color Ribbons

YMCK - 1000 Yield

YMCKK - 750 Yield

YMCKP Peel Off Ribbon - 750 Yield

YMCKU UV - 750 - Yield

InTM Retransfer Film - 1000 Yield

Physical Specification

Height	335mm	Without Card Stacker
Width	343mm	Without Card Stacker
Depth	322mm	Without Card Stacker
Weight	13.5 KG	

Interface

USB2.0 (Hi-speed / Full Speed)
Ethernet (100BASE-TX / 10BASE-T)

Options

Flipper Unit
250 Input Hopper

Operating Environment Conditions

Temperature: 15°C to 30°C
Humidity: 35% to 70% (YMCK ink, No Condensation)

Electrical

3.5A (100V system) 1.6A (220V system)
310W (maximum power when all options are installed)

Card Specification

Card Thickness 10-40mil
Card Size ISO 7810 Format, CR80, ID-1
Card Material: PVC, PC, PET, PET-G
Technology Cards Contact and or Contactless with and Without Mag Stripe



KIS Global GmbH
Niederlasser Lohweg 18, 40547 Düsseldorf, Germany
www.kisglobal.com



Pioneering **SMART**™ Business Operations